

Please type a plus sign (+) inside this box → ☐

PTO/SB/05 (12/97) Approved for use through 09/30/00. OMB 0651-0032

Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No.	15886-210	Total Pages	37
First Named Inventor or Application Identifier			
F. Canova/Method and Apparatus for Software Control of Viewing Parameter			
Express Mail Label No.	EL322090709US		

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO: Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

- | | |
|---|---|
| <p>1. <input type="checkbox"/> Fee Transmittal Form
(Submit an original, and a duplicate for fee processing)</p> <p>2. <input checked="" type="checkbox"/> Specification [Total Pages 30]
(preferred arrangement set forth below)</p> <ul style="list-style-type: none">- Descriptive title of the Invention- Cross References to Related Applications- Statement Regarding Fed sponsored R&D- Reference to Microfiche Appendix- Background of the Invention- Brief Summary of the Invention- Brief Description of the Drawings- Detailed Description- Claim(s)- Abstract of the Disclosure <p>3. <input checked="" type="checkbox"/> Drawing(s) (37 CFR 1.152) [Total Sheets 3]</p> <p>4. <input checked="" type="checkbox"/> Oath or Declaration (unsigned) [Total Pages 3]</p> <p>a. <input type="checkbox"/> Newly executed (original or copy)</p> <p>b. <input type="checkbox"/> Copy from a prior application (37 CFR 1.63(d))
(for continuation/divisional with Box 17 completed)
[Note Box 5 below]</p> <p>i. <input type="checkbox"/> <u>DELETION OF INVENTOR(S)</u>
Signed statement attached deleting
inventor(s) named in the prior application,
see 37 CFR 1.63(d)(2) and 1.33(b).</p> <p>5. <input type="checkbox"/> Incorporation By Reference (useable if Box 4b is checked)
The entire disclosure of the prior application, from which
a copy of the oath or declaration is supplied under Box 4b,
is considered as being part of the disclosure of the
accompanying application and is hereby incorporated by
reference therein.</p> | <p>6. <input type="checkbox"/> Microfiche Computer Program (Appendix)</p> <p>7. Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)</p> <p>a. <input type="checkbox"/> Computer Readable Copy</p> <p>b. <input type="checkbox"/> Paper Copy (identical to computer copy)</p> <p>c. <input type="checkbox"/> Statement verifying identity of above copies</p> <p>8. <input type="checkbox"/> Assignment Papers (cover sheet & documents(s))</p> <p>9. <input type="checkbox"/> 37 CFR 3.73(b) Statement [] Power of Attorney
(when there is an assignee)</p> <p>10. <input type="checkbox"/> English Translation Document (if applicable)</p> <p>11. <input type="checkbox"/> Information Disclosure Statement (IDS)PTO-1449 [] Copies of IDS Citations</p> <p>12. <input type="checkbox"/> Preliminary Amendment</p> <p>13. <input checked="" type="checkbox"/> Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)</p> <p>14. <input type="checkbox"/> Small Entity Statement filed in prior application, Statement(s) [] Status still proper and desired</p> <p>15. <input type="checkbox"/> Certified Copy of Priority Document(s)
(if foreign priority is claimed)</p> <p>16. <input type="checkbox"/> Other:</p> |
|---|---|

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No. ____/____

16. CORRESPONDING ADDRESS

☐ Customer Number of Bar Code Label 021971 or ☒ Correspondence address below
(Insert Customer No. or Attach bar code label here)

NAME	Henry J. Groth				
ADDRESS	WILSON SONSINI GOODRICH & ROSATI 650 Page Mill Road				
CITY	Palo Alto	STATE	California	ZIP CODE	94304-1050
COUNTRY	USA	TELEPHONE	(650) 493-9300	FAX	(650) 493-6811

SUBMITTED BY

Typed or

Printed Name Henry J. Groth

Signature

Henry J. Groth

Reg. Number 39,696

Date April 22, 1999

UNITED STATES PATENT APPLICATION

OF

FRANCIS JAMES CANOVA, JR., AND ROBERT GREGORY TWISS

FOR

**METHOD AND APPARATUS FOR SOFTWARE CONTROL OF VIEWING
PARAMETERS**

PREPARED BY WILSON SONSINI GOODRICH & ROSATI

CROSS REFERENCE TO RELATED APPLICATION

This application relates to and incorporates herein by reference as if fully set forth herein
5 United States patent application serial number 09/201,650, entitled "Button Pivot Bar," filed
November 30, 1998, having inventors Robert Gregory Twiss, Ricardo A. Penate, Amy Aimei Han,
and Traci Angela Neist.

BACKGROUND OF THE INVENTION

Field of Invention

The present invention generally relates to control of viewing parameters for an image screen.
More particularly, the invention relates to viewing parameter control for a portable computer image
screen.

Description of Related Art

Effective and easy user control of viewing parameters, such as contrast, for a portable
computer image screen is a problem. Previous solutions include a mechanically actuated thumb-
wheel (e.g., the PalmPilot™ portable computer and the Palm III™ portable computer) and a
20 mechanically actuated linear "slider" for contrast control. These actuators use mechanical
potentiometers to adjust the screen contrast. One disadvantage of the mechanically actuated thumb-
wheel solution as used for small, portable devices, such as the Palm III, has been that accidental
adjustment of contrast occurs frequently because of contact between the thumb wheel and pockets

and/or carrying cases.

The mechanical approaches are also typically complex, have relatively high failure rates and require special manufacturing operations (e.g., hand soldering).

Patent No. 5,703,661, issued to Wu on December 30, 1997 describes a device with contrast control. The '661 device provides an on-screen adjustment bar that indicates the status of the adjustment. But, the '661 control apparatus still uses a rotary input signal processor to make the actual adjustment, and therefore does not solve the accidental adjustment problem for portable computers.

None of the prior art apparatus and methods provides contrast control in a portable computer that solves the problem of inadvertent adjustment of the contrast while transporting the portable computer.

SUMMARY OF THE INVENTION

Various embodiments of the invention provide a method for software contrast control and a portable computer implementing the software contrast control. The invention eliminates the problem of inadvertent adjustment that exists for slider and rotary input mechanisms for contrast adjustment of portable computers. Various embodiments of the invention include a portable computer having a dedicated button for activating a graphical contrast control user interface. In other embodiments, the contrast control user interface is replaced by other viewing parameter adjustment user interfaces, or a general viewing parameter adjustment user interface covering more than one viewing parameter. Such an interface can be used to adjust color, resolution and/or brightness of a portable computer. The contrast control can be initiated by a single interaction with a mechanical button, for example a pressing of a dedicated button.

One aspect of the invention provides a method for adjusting contrast levels (or values) for an image screen disposed on a portable computer. The method can be used for adjusting other viewing parameters. The method includes a processor disposed in the portable computer receiving an activation signal from a first input mechanism. The activation signal is for viewing parameter control. Responding to the activation signal, a program for viewing parameter control displays graphical user interface elements for viewing parameter control on the image screen.

The method continues with the processor receiving an adjustment signal indicating adjustment from prior values of the viewing parameter to new values of the viewing parameter. The method continues further with the processor responding to the adjustment signal by adjusting the values of viewing parameter for the image screen to the new values. In some embodiments, the method includes activating a contrast control hardware button by pressing the button one time prior to the receiving of the activation signal. More generally, the activating can include applying a single interaction to a first input mechanism.

A second aspect of the invention provides a portable computer having a contrast control button. Activation of the button causes the contrast control graphical user interface elements to appear. The user can adjust the contrast on the portable computer using one or more of the contrast control graphical user interface elements.

BRIEF DESCRIPTION OF THE FIGURES

Figure 1 illustrates a functional block diagram of a portable computer representing an embodiment of the invention.

Figure 2 illustrates a portable computer screen displaying a contrast control dialog window.

Figure 3 shows a flow diagram illustrating a method of viewing parameter control

representing an embodiment of the invention.

DETAILED DESCRIPTION

Various embodiments of the invention include a method for software control of contrast for a display, and a portable computer implementing software control of contrast. The method and the portable computer can be used for the control of other viewing parameters including brightness, color, image screen resolution, zoom factor, or any other parameter that changes the appearance of information displayed on an image screen. For the embodiments described by Figure 1 through Figure 3, the viewing parameter is contrast. Importantly in these embodiments, a single contrast control hardware button on the portable computer is pushed to display a graphical user interface for adjusting contrast. The user can then adjust the contrast using a graphical slider on the portable computer's touch sensitive screen. More generally, software control of a viewing parameter can be initiated by a single interaction with a hardware button, or other input mechanism.

In some embodiments, graphical user interface elements for adjusting the contrast are promptly displayed on the image screen after the user presses the dedicated hardware button. The method can be used for viewing parameters other than contrast as discussed below. The method can be used for any apparatus having an image screen.

From a user interface perspective, previous implementations using only software to adjust viewing parameters often hide the viewing parameter control graphics under multiple layers of menus. Such implementations include contrast, brightness and color adjustment for television and computer monitors, and other apparatus having image screens.

Because prior art contrast control schemes often require navigation through multiple menu selections before a user is able to make the contrast adjustment, these schemes are characterized by a

greater likelihood of user error and user frustration. Even worse, the use of multiple menus on a screen with less than optimal contrast, in order to adjust the contrast, can be very difficult. Especially when the contrast is so poor that each menu selection amounts to little more than guesswork.

5 The problems associated with multiple menu navigation have been overcome by various embodiments of the invention by using a dedicated button on the portable computer that goes directly to the viewing parameter control portion of the software. Additionally, the viewing parameter control application can be implemented in the form of a pop-up menu, which is overlaid "on top of" existing display activity. The pop-up menu provides a single screen for viewing parameter adjustment, instead of requiring navigation through a series of menus. Further, as mentioned below, two means of viewing parameter adjustment input can be provided - either graphical user interfaces disposed on the touch responsive image screen or one or more hardware buttons.

Portable Computer Including Software Viewing Parameter Control

Various embodiments of the invention provide a portable computer 100 having software contrast control. In some embodiments, the portable computer can have software control of other viewing parameters performed according to the methods described below in the Example Method for Software Control of Viewing Parameters section. Some embodiments of the portable computer 100 are depicted in Figures 1 and 2. Figure 1 illustrates some components typically disposed in the portable computer 100. Figure 2 illustrates a portable computer 100 image screen displaying a contrast control dialog window. Figure 2 is based on the Palm Computing portable computer.

The portable computer 100 can include a contrast control button 110, a processor 120, a

memory 130, a display 140, and a digitizer 150. The display 140 can be a touch-sensitive image screen, and is adapted to display items of information at viewing parameter levels. The processor 120 can be a Dragonball™ -EZ (MC68EZ328) processor from Motorola, or any other personal systems embedded processor.

5 The memory 130 can include an operating system 132, an existing application 134, and a contrast control dialog window program 136. The memory 130, including the data and programs stored in the memory, is addressable by the processor 120. In some embodiments of the invention the operating system (OS) 132 comprises the PalmOS™ operating system available from 3Com. In embodiments providing control for a viewing parameter other than contrast, a viewing parameter dialog window program can provide one or more graphic user interface (GUI) elements for control of the corresponding viewing parameter.

 The processor 120 and the memory 130 can be coupled to respond to the single interaction with the contrast control button 110 by displaying contrast control GUI elements on the display 140. The processor 120 and the memory 130 can also be coupled to respond to inputs applied to the viewing parameter control GUI elements by adjusting the display 140 drive voltages. The inputs can include one or more of selecting and adjusting one or more of the viewing parameter control GUI elements.

 The digitizer 150 can be adapted to respond to contact against the display 140 by sending a signal to the contrast control dialog window program 136. The contrast control dialog window
20 program 136 can be adapted to respond to the signal by adjusting the display 140 drive voltages.

 Some embodiments of the portable computer 100 provide software contrast control using the contrast control method described in the Example Method for Software Control of Viewing Parameters section below. In other embodiments, the portable computer is capable of implementing

software viewing parameter control for brightness levels, color levels (i.e., color bit depth), color versus monochrome, and screen resolution (number of pixels per inch). Appropriate adjustment of the screen resolution parameter can provide energy savings for low-resolution users and prolong battery life because fewer pixels can be used. One example of a low-resolution user is one that uses graphics such as icons to execute programs on the portable computer. Lower resolution for such users provides for adequate viewing of the icon compared to the resolution level required to view text.

The contrast control button 110 (an example of a “first input mechanism”), is connected to the processor 120 and is adapted to initiate contrast adjustment in response to a single interaction. The contrast control button 110 can comprise a momentary single pole single throw (SPST) switch. The contrast control button 110 can respond to a single pressing by initiating contrast adjustment.

For some embodiments, the SPST switch is adapted to respond to user manipulation thereof by transmitting an activation signal to the contrast control dialog window program 136. The contrast control dialog window program 136 is adapted to respond to the activation signal by displaying a contrast control dialog window on the image screen.

As illustrated in Figure 2, some embodiments of the portable computer 100 can include a power button 215, a down scrolling button 225, an up scrolling button 230, and a plurality of application buttons 235 (four shown in Figure 2). The portable computer can also include screen-viewed application buttons 240, an adjustment bar 250, a slider 255, a circle-i button 260, a “done” button 270 and an “Address List” pull-down menu 280.

For some embodiments, the contrast control button 110 is disposed on the outer surface of the portable computer 100 on the left side of the top surface. In other embodiments, the contrast control button can be located on a side surface, the bottom surface, the top surface, or the back

surface of the portable computer 100. A single pressing of the contrast control button 110 initiates the contrast control dialog window program 136.

The portable computer 100 can include a digitally controlled circuit adapted to apply the display 140 drive voltages to the pixels. The contrast control dialog window program 136 can be adapted to provide signals to the digitally controlled circuit. These signals can be generated in response to a selection or adjustment of one or more of the viewing parameter control GUI elements.

For embodiments depicted by Figure 2, after the pressing the contrast control button 110, a contrast control dialog window program 136 causes the display of the software contrast control dialog window 245 on the display 140. If the portable computer 100 is off, then pressing the contrast control button 110 can, in some embodiments, turn the portable computer 100 on as well as cause the software contrast control dialog window 245 to appear on the display 140. The contrast control dialog window 245 typically includes text and one or more viewing parameter control GUI elements. Contrast adjustments are normally caused by applying input to one or more of the contrast control GUI elements.

The display 140 can be a touch sensitive image screen adapted to provide signals to applications in response to contacting or tapping the display. In response to contacting the display 140, the processor 120 can be adapted to send signals to the memory 130, i.e., the contrast control dialog window program 136. As shown in Figure 2, the viewing parameter control GUI elements can include a virtual slide control, or slider 255, disposed above an adjustment bar 250. In Figure 2, these viewing parameter control GUI elements are disposed in the contrast control dialog window 245.

The adjustment bar 250 shown in Figure 2 extends horizontally across approximately 85 percent of the width of the contrast control dialog window 245. The horizontal extent, or length, of

the adjustment bar 250 can range from slightly larger than the horizontal extent of the slider 255 to nearly 100 percent of the width of the contrast control dialog window 245. The disadvantage of smaller adjustment bar 250 lengths is that the smaller lengths hinder user ability to make finer adjustments to the contrast.

5 The adjustment bar 250 can show a gray scale that is lighter at one end of the adjustment bar and becomes darker as the adjustment bar extends to the other end. The gray scale provides the user with an on-screen indication of the direction of the contrast adjustment resulting from a particular movement of the slider 255.

10 The slider 255 is disposed above the adjustment bar 250, so that the adjustment bar portion disposed directly below the slider is covered by the slider. For the embodiment shown in Figure 2, the slider 255 includes a “thumb” graphic that is similar in appearance to sliders used for car ventilation system controls and audio equalizers. The slider 255 shown in Figure 2 has a horizontal extent, or width, that is typically smaller than the length of the adjustment bar 250. But, the slider 255 width is sufficiently large to enable a user to easily interact with the slider. The slider 255 shown in Figure 2 extends farther both upwards and downwards than the adjustment bar 250.

15 The slider 255 is typically adjusted by contacting the display 140 with a stylus, pen, finger or any other implement capable of contacting the display 140 with reasonably accurate location precision. Contacting the display 140 to the left of the slider 255 can decrease the contrast incrementally, and contacting the display 140 to the right of the slider can increase the contrast
20 incrementally.

 Holding the implement down on the adjustment bar 250 causes the slider 255 to repeatedly move toward the location at which the implement is in contact with the display 140 until the slider moves directly under the implement. When an implement touches the display 140 directly above the

slider 255, the slider can be dragged by movement of the implement as long as the implement maintains contact with the display.

When the viewing parameter setting reaches a minimum or a maximum value, the viewing parameter can no longer be adjusted past the extreme value, and a warning sound is produced for some embodiments of the invention. The use of a warning sound is especially useful for informing the user of the extreme viewing parameter situation, because the display 140 can be difficult to view at either of the extreme viewing parameter settings.

For the embodiment shown in Figure 2, the contrast control dialog window 245 also includes the circle-i button 260 and the dialog “done” button 270.

In some embodiments, contacting the dialog “done” button 270 causes the portable computer 100 to remove the contrast control dialog window 245 from the display 140 and to exit the contrast control dialog window program 136. Also, contacting one of the screen-viewed application buttons 240, such as the application launcher icon, the menu icon, the calculator icon, or the find icon, causes dismissal of the contrast control dialog window program 136. The contrast control dialog window program 136 is also dismissed by a second pressing of the contrast control button 110.

Note that when the contrast control dialog window 245 is provided on the display 140, contacting the display anywhere other than the adjustment bar 250, the slider 255, the dialog “done” button 270, or the circle-i button 260 can cause the portable computer 100 to emit a beep. The beep can be provided by a viewer module of the portable computer 100, and assists the user in locating the slider 255 and the adjustment bar 250 when these viewing parameter control GUI elements are not observable on the display 140.

The portable computer 100 can use other input mechanisms (e.g., up scrolling button 230 and down scrolling button 225) to adjust the viewing parameters. The other input mechanisms can be

adapted to respond to inputs applied thereto by providing indications of viewing parameter level (or value) adjustment to the contrast control dialog window program 136. Responsive to the input applied to the other input mechanisms, the contrast control dialog window program 136 causes an adjustment of the viewing parameter level.

5 For user convenience and for conditions where on-screen viewing parameter control is not possible due to low battery or any other inadequate display condition, an optional back-up user contrast adjustment can be performed using the second input mechanism. The second input mechanism can be one or more hardware buttons. For some embodiments as shown in Figure 2, the viewing parameter adjustment hardware buttons are the up scrolling button 230 and down scrolling button 225.

Example Method for Software Control of Viewing Parameters

Various embodiments of the contrast control method 300 are depicted in Figure 3. The contrast control method 300 includes the processor 120 receiving a contrast control button signal (block 310) from the contrast control button 110. The button signal acts as an activation signal for contrast control. The location of the contrast control button 110 for some embodiments is shown in Figure 2. In other embodiments, the contrast control button 110 can be replaced by any input mechanism capable of providing an activation signal to the processor 120.

20 The contrast control dialog window program 136 responds to the activation signal by displaying (at block 350) the contrast control dialog window 245 on the display 140. The contrast control dialog window 245 can include a slider 255 coupled to an adjustment bar 250.

In some embodiments, the processor 120 receives a contrast adjustment signal (at block 360) indicating adjustment from prior contrast levels to adjusted levels. In other embodiments, the

adjustment signal can relate to a different viewing parameter.

The processor 120 responds to the adjustment signal by adjusting the contrast levels for the display 140 to the adjusted levels at block 370. For embodiments where the adjustment signal corresponds to a viewing parameter other than contrast, the processor 120 adjusts the levels of the corresponding viewing parameter to the adjusted levels.

In some embodiments, the contrast control method 300 includes activating the contrast control button 110 by a single pressing of the contrast control button prior to the receiving of the contrast control button signal at block 310. In other embodiments, the viewing parameter control method includes activating a contrast control button 110 by applying a single interaction to the contrast control button 110. The single interaction can include a specified movement for a push-activated switch, a rotation actuated switch, a slide activated switch, or any other activation mechanism.

In some embodiments, the activating occurs after the portable computer 100 has been powered-up. The user can power up the portable computer 100 depicted in Figure 2 by pressing the power button 215, or one of the application buttons 235, prior to activating the contrast control button 110. Masking the activating signal from the processor 120 when the portable computer is off eliminates the possibility powering up the portable computer 100 by accidentally pressing the contrast control button 110.

In other embodiments, the activating can occur when the portable computer 100 is either powered up, or off. For these embodiments, after receiving the contrast control button signal (at block 310), there is no masking of the activation signal from the processor 120, or the activation signal masking occurs only in certain conditions, e.g., low battery energy. When the portable computer is off, upon receipt of the activation signal, the portable computer 100 determines whether

the portable computer is on (at block 320). Activating the contrast control button 110 with the portable computer 100 powered off can result in the portable computer powering-up and starting the last (existing) application 134 that was running before the portable computer was last turned off (at block 330).

5 The displaying of the contrast control dialog window 245 (at block 350) can include overlaying the contrast control dialog window on top of graphics from the last (existing) application 134 shown on the display 140 prior to the activating. For embodiments where the activation of the contrast control button 110 powers-up the portable computer 100, the portable computer starts the last (existing) application 134 that was running before the portable computer was turned off. The portable computer 100 can then display the existing application 134 graphics on the display 140 (at block 340), before displaying the contrast control dialog window 245 (or other viewing parameter control GUI elements) on top of the last application graphics (at block 350). One example of the overlaying of the contrast control dialog window 245 is shown in Figure 2, where the last application graphics include the “Address List” pull-down menu 280.

15 In some embodiments, the portable computer 100 responds to receiving the viewing parameter control activation signal by switching the display 140 to a preset viewing parameter level. For example, the user can select the preset viewing parameter level using a preference setting application to provide a preferred viewing condition. The preset contrast level can be a minimum viewable contrast level, or a maximum viewable contrast level. Using a preset contrast level
20 improves the user experience by enabling the user to proceed with contrast control from a familiar routine starting point. In addition, if the user finds a particular viewing parameter level that provides optimal viewing, the user can set the viewing parameter level for optimal viewing and thereby minimize the need to further adjust the viewing parameter.

Adjustment from prior viewing parameter levels to adjusted viewing parameter levels can be indicated by interaction with one or more of the viewing parameter control GUI elements. The interaction can include selecting or adjusting one or more of the viewing parameter control GUI elements, or a combination of selecting and adjusting one or more of the GUI elements.

5 The interactions can include tapping the display 140 with an implement on locations disposed on the adjustment bar 250 on either side of the slider 255. The interactions can also include touching the display 140 with an implement directly above the slider 255, and while maintaining contact with the display 140 moving the implement along the adjustment bar 250.

10 In response to the indicating of the adjustment, the processor adjusts the contrast levels on the display 140 to the adjusted levels (at block 370). In some embodiments, the contrast control dialog window program 136 translates instructions from the user, either via direct adjustment of the slider 255 on a touch sensitive display 140, or via hardware buttons. In response to the user adjustment indications, the processor 120 transmits signals to manipulate digitally controlled electronics that adjust the contrast (at block 370) for the display 140 in accordance with the user's implicit commands. The viewing parameter adjustment can be accomplished by adjusting display 140 drive voltages, e.g., for brightness, color, and contrast viewing parameters.

15 After the viewing parameter adjustment, a determination can be made regarding the need for further viewing parameter level adjustment (at block 375). If no further adjustment is needed, the portable computer 100 exits the contrast control (viewing parameter) dialog window program 136 and returns to the last application (at block 380). Returning to the last application, at block 380, can be caused by selection of a "done" button 270, shown in Figure 2, or by pressing the contrast control button 110.

20 Some embodiments of the portable computer 100 provide a second input mechanism with

which the user can interact to provide a contrast adjustment signal, as an alternative to interacting with the viewing parameter control GUI elements. This second input mechanism can be used when the display 140 does not provide an adequate image of the viewing parameter control GUI elements to enable a user to make adjustment thereto, or simply because the user prefers to use the second input mechanism.

The second input mechanism can include the up scrolling button 230 and the down scrolling button 225. The interaction with the second input mechanism occurs after activating the contrast control button 110, and prior to receiving the adjustment signal. The requirement for the interaction to occur after activating the contrast control button 110 arises for embodiments, such as the Palm V™ from 3Com Palm Computing, where the second input mechanism provides signals for different functions when applications different than the existing application are running. The interaction with the second input mechanism causes the processor 120 to receive the adjustment signal at block 360. The processor 120 then sends a signal corresponding to the adjustment signal to the memory 130.

Interacting with the up scrolling button 230 can include a short pressing of the first pressing region e.g., for a period of time less than approximately 500 milliseconds. For some embodiments of the invention provided by Palm Computing, the maximum pressing time for a short pressing can be modified by the user to a value different than 500 milliseconds. The short pressing of the up scrolling button 230 transmits an indication of an incremental upward adjustment of the contrast levels to the contrast control dialog window program 136.

Interacting with the up scrolling button 230 can include a longer pressing of the first pressing region e.g., for a period of time greater than approximately 500 milliseconds. The longer pressing of the up scrolling button 230 transmits an indication of a large upward adjustment of the viewing parameter levels to the contrast control dialog window program 136. The large upward adjustment

is more than approximately twice the magnitude of the incremental upward adjustment.

The down scrolling button 225 works in a manner similar to the up scrolling button 130, except to decrease the viewing parameter value.

5 Alternate Embodiments

In other embodiments, the second input mechanism can include a rotational input means, or a sliding input means. The input means can include variable potentiometers adapted to provide a signal to the contrast control dialog window program 136 corresponding to the adjusted position of the input means.

In some embodiments, the second input mechanism includes a press and rotate input mechanism adapted to provide a first signal by pressing the press and rotate input mechanism and a second signal (or series of second signals) by rotating the press and rotate input mechanism. One example of a press and rotate input mechanism is the Panasonic EVQWK5001 encoder switch. The press and rotate input mechanism can replace the contrast control button 110 and be located at the top left of the portable computer 100. The first signal can be used as the activation signal for viewing parameter control, and each second signal can provide an adjustment signal for the corresponding viewing parameter.

Alternatively, the press and rotate input mechanism can be disposed on either side of the portable computer 100, and can work in conjunction with the contrast control button. For some of these embodiments the first signal can be the exclusive hardware mechanism for exiting the contrast control dialog window program 136. In other embodiments, either a second pressing of the contrast control button 110, or a pressing of the press and rotate input mechanism can exit the contrast control dialog window program.

When the display of the viewing parameter control GUI elements is adequate, then the contrast adjustment is typically made by interacting with the GUI elements. For some embodiments, the viewing parameter adjustment can be made by interacting with the second input mechanism even when the viewing parameter control GUI elements are adequately displayed.

5 In an alternate embodiment, the interactions for adjusting the viewing parameter can include selecting one or more viewing parameter control GUI elements, where the elements represent a particular group of viewing parameter settings. A series of such selectable viewing parameter control GUI elements can be provided in a list or a menu. The viewing parameter control GUI elements can be identified on the display 140 using qualitative descriptors, such as maximum contrast, very high contrast, high contrast, midrange contrast, low contrast, etc. Selectable viewing parameter control GUI elements can also be identified on the display 140 using quantitative descriptors such as 100% contrast, 90% contrast, etc. Selection of the appropriate contrast level can be achieved by tapping the display 140 above the corresponding GUI element.

10 In some embodiments, a rocker switch (not shown) can replace the separate up and down scrolling buttons (225 and 230). Various embodiments of the rocker switch are described in United States patent application serial number 09/201,650, filed November 30, 1998 incorporated herein by reference as if fully set forth herein. The rocker switch and the up and down buttons can be integrally formed from a single member. The rocker switch has an integrally formed fulcrum or pivot bar that isolates the movement of each scrolling button to ensure that pressing of the rocker switch does not inadvertently cause simultaneous actuation of both scrolling buttons.

20 In some embodiments, the back-up user viewing parameter adjustment can be performed using a single hardware button for viewing parameter adjustment. For example, the contrast control button 110 can have three states. The first state can have the viewing parameter control application

on with the viewing parameter adjustment hardware button in a viewing parameter increase adjustment mode, i.e., pressing the single viewing parameter adjustment hardware button can only increase the viewing parameter. The second state has the viewing parameter control application on with the hardware button for viewing parameter adjustment in a viewing parameter decrease adjustment mode. The contrast control button 110 can be adapted to respond to a single pressing thereof by merely toggling the state between the increase only and decrease only modes. For this embodiment, two consecutive pressings of the contrast control button 110 are required to reach the third state where the viewing parameter control application is exited.

In some alternate embodiments, the display 140 includes portions adapted for illumination by groups of pixels enabling the contrast control method 300 to apply the contrast (or viewing parameter) adjustments to one or more selected portions of the display 140. The viewing parameter levels can vary in response to display 140 drive voltages. Different groups of the pixels can have different display 140 drive voltages and corresponding viewing parameter levels. A first portion of the display 140 is illuminated by a first group of pixels.

For these embodiments, adjusting the contrast levels, at block 370, can include maintaining the display 140 drive voltages at low levels for one or more of the groups of pixels, and adjusting the display voltages to adjusted voltages corresponding to the graphical user interface adjusted contrast levels for the first group of pixels. The first portion can cover less than approximately twenty-percent of the display 140.

In some embodiments, the portable computer 100 can display selected information only on the first portion. This selective viewing parameter control technique can save power by reducing the drive voltage level to a minimum for most of the display 140 while providing sufficient viewing parameter levels for viewing information displayed in the selected portions, e.g., the first portion.

By providing different viewing parameter levels for different portions of a display 140, the portable computer 100 can provide excellent resolution for portions of the display where such resolution is necessary e.g., small font text and detailed graphics images. At the same time, the portable computer 100 can save battery life, or recharge frequency, by keeping portions of the screen with no images dark.

Some portable computers 100 are connected to multiple screen displays 140. For these portable computers 100, the groups of the pixels can correspond to the different displays 140.

All the disclosed embodiments of the invention described herein can be realized and practiced without undue experimentation. Although the best mode of carrying out the invention contemplated by the inventors is disclosed above, practice of the invention is not limited thereto. Accordingly, it will be appreciated by those skilled in the art that the invention may be practiced otherwise than as specifically described herein.

For example, the individual components need not be formed in the disclosed shapes, or assembled in the disclosed configuration, but could be provided in virtually any shape, and assembled in virtually any configuration. Furthermore, all the disclosed elements and features of each disclosed embodiment can be combined with, or substituted for, the disclosed elements and features of every other disclosed embodiment except where such elements or features are mutually exclusive.

It will be manifest that various additions, modifications and rearrangements of the features of the invention may be made without deviating from the spirit and scope of the underlying inventive concept. It is intended that the scope of the invention as defined by the appended claims and their equivalents cover all such additions, modifications, and rearrangements. The appended claims are not to be interpreted as including means-plus-function limitations, unless such a limitation is

CLAIMS

1 1. A method for adjusting levels of a viewing parameter for an image screen disposed on a
2 portable computer, the method comprising:
3 a processor disposed in the portable computer receiving an activation signal for viewing
4 parameter control from a first input mechanism, the activation signal corresponds to a single
5 interaction with the first input mechanism;
6 responsive to the activation signal, a program displaying graphical user interface elements
7 adapted for viewing parameter control on the image screen;
8 the processor receiving an adjustment signal indicating adjustment from prior values of the
9 viewing parameter to new values of the viewing parameter; and
10 responsive to receiving the adjustment signal, the processor adjusting the values of the
11 viewing parameter for the image screen to the new value.

1 2. The method of claim 1, wherein prior to the receiving of the adjustment signal, the
2 method includes:
3 receiving an interaction signal corresponding to an interaction with one or more of the
4 graphical user interface elements; and
5 responsive to receiving the interaction signal, the program causing a generation of the
6 adjustment signal, the new values corresponding to the interacting.

1 3. The method of claim 2, wherein the graphical user interface elements include an
2 adjustment bar and a slider disposed along the adjustment bar, the image screen adapted to provide
3 signals to programs in response to at least one contact with the image screen.

1 4. The method of claim 3, wherein interacting with the graphical user interface elements
2 includes one or more of:

3 a contact with the image screen by an implement on a location disposed on the adjustment
4 bar other than directly above the slider; and

5 a contact with the image screen by an implement directly above the slider, and while
6 maintaining contact with the image screen moving the implement along the adjustment bar.

1 5. The method of claim 1, wherein the image screen includes pixels, the pixels having
2 output levels, and the adjusting includes:

3 adjusting image screen drive voltages to adjusted voltages corresponding to the new values,
4 the pixels connected to the image screen drive voltages; and

5 the pixel output levels responding to the adjusted voltages by providing an adjusted image.

1 6. The method of claim 5, wherein the image screen includes portions adapted for
2 illumination by groups of pixels including a first portion configured for illumination by a first group
3 of pixels, and wherein the adjusting includes:

4 maintaining the image screen drive voltages at low levels for one or more of the groups of
5 pixels, and

6 adjusting the image screen voltages to adjusted voltages corresponding to the new values for

7 the first group of pixels, the first portion covering less than approximately twenty-percent of the
8 image screen, and wherein the method includes
9 the portable computer displaying selected information only on the first portion.

1 7. The method of claim 1, wherein prior to the receiving of the adjustment signal the
2 method includes:

3 receiving an interaction signal from a second input mechanism to indicate adjustment of the
4 values of the viewing parameter to new values; and

5 responsive to the interaction signal from the second input mechanism, the processor sending
6 a signal corresponding to the adjustment signal to a memory disposed in the portable computer.

1 8. The method of claim 7, wherein the second input mechanism comprises an up
2 scrolling button having a first pressing region and down scrolling button having a second pressing
3 region, and the scrolling buttons adapted to provide adjustment indications for the values of the
4 viewing parameter to the program;

5 the interacting with the second input mechanism includes one or more of:

6 pressing the first pressing region for a period of time less than approximately 500
7 milliseconds thereby providing an indication of an incremental upwards adjustment of the levels of
8 the viewing parameter to the application;

9 pressing the first pressing region for a period of time greater than approximately 500
10 milliseconds, thereby providing an indication of a large upwards adjustment of the levels of the
11 viewing parameter to the application, the large upwards adjustment more than approximately twice
12 the magnitude of the incremental upwards adjustment.

1 9. The method of claim 1, wherein:
2 the second input mechanism includes a rotate and push switch; and
3 the method includes, the rotate and push switch responding to a rotation of the rotate and
4 push switch by providing adjustment indications for the values of the viewing parameter to the
5 program.

1 10. The method of claim 1, wherein the first input mechanism comprises a button
2 disposed on the portable computer, and the single interaction with the button comprises a pressing of
3 the button.

1 11. The method of claim 1, wherein responsive to the portable computer in a power off
2 state prior to the activating, the activating includes powering-up the portable computer.

1 12. The method of claim 1, wherein prior to the displaying, the method includes the
2 portable computer responding to the activation signal by initiating the program.

1 13. The method of claim 1, wherein the displaying includes overlaying one or more of the
2 graphical user interface elements on top of graphics shown on the image screen prior to the
3 activating.

1 14. The method of claim 1, wherein the viewing parameter includes one of contrast,
2 brightness, color, and screen resolution.

1 15. The method of claim 1, further comprising the portable computer responding to
2 receiving the activation signal by switching the image screen to a preset value of the viewing
3 parameter.

1 16. A portable computer comprising:
2 an image screen adapted to display items of information at levels of a viewing parameter;
3 a first input mechanism adapted to initiate adjustment of viewing parameter values in
4 response to a single interaction with the first input mechanism;
5 a processor; and
6 a memory coupled with the processor to:
7 respond to the single interaction by displaying at least one graphical user interface
8 element adapted for adjusting the viewing parameter values; and
9 respond to inputs applied to the graphical user interface elements by adjusting the
10 values of the viewing parameter, each of the inputs including at least one of selecting and adjusting
11 at least one of the graphical user interface elements.

1 17. The portable computer of claim 16, wherein the portable computer comprises a
2 connected organizer including:
3 a program for viewing parameter control disposed in the memory; and
4 a digitizer adapted to respond to contact with the image screen by sending an interaction

5 signal to the program; and

6 wherein the program is adapted to respond to the interaction signal by causing adjustment of
7 at least one graphical user interface element to indicate new viewing parameter values.

1 18. The portable computer of claim 17, wherein:

2 the viewing parameter is contrast;

3 the first input mechanism comprises a button adapted to initiate contrast adjustment

4 responsive to a single pressing of the button; and

5 the graphical user interface elements include an adjustment bar and a slider disposed above
6 the adjustment bar; and

7 and the portable computer includes:

8 an operating system disposed in the memory, the program disposed in the operating;

9 the program adapted to respond to the interaction signal by causing adjustment of the
10 image to the new viewing parameter values;

11 a power button adapted to power-up the portable computer by pressing of the power button;

12 at least one application button, each application button adapted to start a corresponding
13 application by pressing of the application button; and

14 a second input mechanism adapted to respond to inputs applied to the second input
15 mechanism by providing indications of adjustment of values of the viewing parameter to the
16 memory.

1 19. The portable computer of claim 16, wherein the first input mechanism comprises a

2 button adapted to initiate contrast adjustment responsive to a single pressing of the button.

1 20. The portable computer of claim 16, wherein the viewing parameter includes one of
2 contrast, brightness, colors, and screen resolution.

1 21. The portable computer of claim 16, including a second input mechanism adapted to
2 respond to inputs applied to the second input mechanism by providing indications of adjustment of
3 values of the viewing parameter to the memory; and wherein responsive to the inputs applied to the
4 second input mechanism, the processor adapted to adjust the values of the viewing parameter.

1 22. The portable computer of claim 21, wherein the second input mechanism includes a
2 rotate and push switch adapted to respond to a pressing applied to the rotate and push switch by
3 exiting the program for viewing parameter control.

1 23. The portable computer of claim 16, wherein:
2 in response to contact with the image screen, the processor is adapted to send signals to the
3 memory; and
4 the graphical user interface elements include an adjustment bar and a slider disposed above
5 the adjustment bar.

1 24. The portable computer of claim 16, wherein the first input mechanism comprises a
2 single momentary single pole single throw (SPST) switch.

1 25. The portable computer of claim 16, wherein the image screen includes pixels, the
2 values of the viewing parameter vary in response to image screen drive voltages, and different
3 groups of the pixels have different image screen drive voltages.

1 26. The portable computer of claim 16, wherein the image screen includes pixels, the
2 values of the viewing parameter vary in response to image screen drive voltages, and more than
3 approximately eighty percent of the pixels have a value of the viewing parameter corresponding to a
4 first image screen drive voltage.

1 27. A portable computer comprising:
2 a screen means for displaying items of information at a set of viewing parameter values;
3 an input means for:
4 initiating adjustment of the set of viewing parameter levels in response to a single
5 interaction with the input means;
6 a processor means connected to the input means; and
7 a memory means, wherein the processor means is coupled with the memory means for:
8 responding to the single interaction by displaying at least one graphical user interface
9 element adapted for viewing parameter control on the screen means in response to the single
10 interaction; and
11 adjusting the screen means drive voltages in response to at least one input, each input
12 is applied to at least one graphical user interface element, each input is applied by one of selecting
13 and adjusting a corresponding graphical user interface element.

ABSTRACT

The invention provides a method for software contrast control and a portable computer
5 implementing software contrast control. The contrast control is initiated by a single interaction
with an input mechanism, for example a pressing of a dedicated contrast control button. The
method can be applied more generally to viewing parameters other than contrast such as
brightness, color bit depth, color versus monochrome, and screen resolution. The method
includes a processor disposed in the portable computer receiving an activation signal from a
10 button or other input mechanism, and displaying viewing parameter adjustment graphics on the
image screen. The method continues with the processor receiving a viewing parameter
adjustment signal and responding to the adjustment signal by adjusting the viewing parameter
levels for the image screen to levels based on the adjustment graphics. The method can include
activating the input mechanism by applying a single interaction to thereto prior to the receiving
15 of the activation signal for viewing parameter control. The portable computer can include a
display, a contrast control hardware button, a processor, and a memory. The viewing parameter
levels vary in response to image screen drive voltages. The processor responds to input applied
to the viewing parameter control graphical user interface elements by adjusting the viewing
parameters. The applying of the input includes one or more of selecting and adjusting one or
20 more of the viewing parameter control graphical user interface elements.




FIGURE 1




FIGURE 2




FIGURE 3

disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulation, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

<u>(Application Serial No.)</u>	<u>(Filing Date)</u>	<u>(Patented, Pending, Abandoned)</u>
<u>(Application Serial No.)</u>	<u>(Filing Date)</u>	<u>(Patented, Pending, Abandoned)</u>

I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith, and to file, prosecute and to transact all business in connection with international applications directed to said invention:

Paul Davis	29,294
John J. Bruckner	35,816
David J. Weitz	38,362
Kent R. Richardson	39,443
David J. Abraham	39,554
U.P. Peter Eng	39,666
Henry Groth	39,696
George A. Willman	41,378
Jinntung Su	42,174
Travis L. Dodd	42,491
Van Mahamedi	42,828
Shantanu Basu	43,318

Address all correspondence to:

Henry J. Groth
Wilson Sonsini Goodrich & Rosati
650 Page Mill Road
Palo Alto, CA 94304

Direct all telephone calls to Henry Groth at (650) 493-9300.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Title 18, United States Code, §1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or
first inventor: Francis James Canova, Jr.

Inventor's signature: _____

Date: _____

Citizenship: U.S.A.

Residence: 3337 Morningview Terrace, Fremont, CA 94539

Post Office Address: Same as above

Full name of second joint
inventor, if any: Robert Gregory Twiss

Inventor's signature: _____

Date: _____

Citizenship: U.S.A.

Residence: 1019 LosTrancos Road, Portola Valley, CA 94028

Post Office Address: Same as above